

RIGHT ANGLE FLEXIBLE LEADS



FIG. R

Figure R is used when spacing requirements are limited. See chart below for the additional dimension the Mighty Watt Plus adds to the sheath length of stock items. When ordering non-stock Fig. R, specify the overall sheath length. High temperature (850° F/450° C) leads are fully flexible from the exit of the sheath. 12" lead wire is standard. Specify additional length.

Non-Stock Right Angle Leads - Fig. R	
Dia.	Minimum Unheated*
1/8"	--
1/4"	1"
5/16"	1-1/2"
3/8"	1-1/2"
1/2"	1-1/2"
5/8"	1-9/16"
3/4"	1-7/8"
15/16"	1-7/8"
1"	1-7/8"
1-1/4"	1-7/8"

* At lead end. Standard cold sections can be increased. Consult Ogden for metric diameter dimensions.

2 Day Shipment Mighty Watt Plus Right Angle Leads - Fig. R	
Dia.	Adds to Length
1/4"	9/16"
3/8"	9/16"
1/2"	5/8"
5/8"	5/8"
3/4"	5/8"

Add 3/8" to above dimensions for total cold section at lead end.

Ordering Number Example:

From Current Stock List:
 1/2" x 5-3/4" 1000W 240V
 MWEJ05N0116
 Add 24" Fig. R Leads
 MWEJ05N0116-R2
 (overall length now 6-3/8")