

## TYPE A SILICONE RUBBER HEATERS

SIZE		EFFECTIVE HEATED AREA (SQ. IN.)	WATTS @ 5 WATTS/SQ. IN.	CATALOG NUMBER @120V*	CATALOG NUMBER @240V*	WATTS @ 10 WATTS/SQ. IN.	CATALOG NUMBER @120V*	CATALOG NUMBER @240V*
W	L							
1	5	3.75	25	SR2031	-	50	SR3126	SR3157
1	6	4.5	30	SR2033	-	60	SR3127	SR3158
1	7	5.4	35	SR2035	-	70	SR3128	SR3159
1	8	6.2	40	SR2037	-	80	SR3129	SR3160
1	9	7.0	45	SR2039	-	90	SR3130	SR3161
1	10	7.8	50	SR2041	SR3100	100	SR3131	SR3162
1	15	11.9	75	SR2043	SR3101	150	SR3132	SR3163
2	2	3.1	20	SR2045	SR3102	40	SR3133	SR3164
2	3	4.9	30	SR2047	SR3103	60	SR3134	SR3165
2	4	6.8	40	SR2049	SR3104	80	SR3135	SR3166
2	6	10.35	60	SR2051	SR3105	120	SR3136	SR3167
2	10	17.4	90	SR2053	SR3106	200	SR3137	SR3168
2	12	21.15	120	SR2055	SR3107	240	SR3138	SR3169
2	16	28.16	160	SR2057	SR3108	320	SR3139	SR3170
3	3	7.35	45	SR2059	SR3109	90	SR3140	SR3171
3	5	12.85	75	SR2061	SR3110	150	SR3141	SR3172
3	8	20.9	100	SR2063	SR3111	240	SR3142	SR3173
3	10	26.55	150	SR2065	SR3112	300	SR3143	SR3174
3	15	40.3	225	SR2067	SR3113	450	SR3144	SR3175
3	20	54	275	SR2069	SR3114	600	SR3145	SR3176
4	4	13.8	80	SR2071	SR3115	160	SR3146	SR3177
4	8	28.8	160	SR2073	SR3116	320	SR3147	SR3178
4	12	43.8	240	SR2075	SR3117	480	SR3148	SR3179
4	20	72	360	SR2077	SR3118	800	SR3149	SR3180
5	5	22.3	125	SR2079	SR3119	250	SR3150	SR3181
5	10	46	250	SR2081	SR3120	500	SR3151	SR3182
5	15	69.7	375	SR2083	SR3121	750	SR3152	SR3183
5	20	93	465	SR2085	SR3122	1000	SR3153	SR3184
10	10	94.7	500	SR2087	SR3123	1000	SR3154	SR3185
10	15	143.4	750	SR2089	SR3124	1500	SR3155	SR3186
10	20	190	950	SR2091	SR3125	2000	SR3156	SR3187

\* 12" silicone leads exiting from edge of heater in center of width.

Ogden standard Type A Silicone Rubber Heaters are available as per the above chart, or as the following parameters:

1. Square or rectangular shape – specify length and width.
2. Silicone leads (specify length) exiting from the edge of heater centered in the width. Lead patch is 1" x 1" (typical).
3. Maximum 10 watts/sq. in. and 240V.
4. Standard Ogden markings.
5. PSA on side opposite lead patch if required.
6. Approval drawings are not required for Type A Silicone Rubber Heaters.
7. Less than standard lead times apply to Type A items.

